

AirKing®

Ventilation Products

SPECIFICATIONS

52" Ceiling Fan with Light

52" BUILDER'S CHOICE CEILING FANS WITH LIGHT

120 Volts, 0.5 amps, 60 hz.

► **FAN BODY**

Powder coated .0035" thick steel body housing.

► **MOTOR**

Permanently lubricated, powerful 3-speed reversible motor.
120 volt, 60 hz, 0.5 amp, 60 watt.

► **UNIT MOUNTING**

Dual mounting. Close to ceiling mounting or Downrod. All mounting hardware including a 4" downrod is included in box.

► **FINISHES**

- 9800 - Polished Brass body
- 9805 - White/Polished Brass body
- 9810 - White body
- 9815 - Antique Brass body



► **PADDLES**

- 9800L - 5 reversible Cherry/Oak paddles
- 9805L - 5 reversible White/Bleached Oak paddles
- 9810L - 5 reversible White/Bleached Oak paddles
- 9815L - 5 reversible Cherry/Dark Oak paddles

► **SINGLE PACK SHIPPING INFO**

- Box Dim 21"x 9^{3/16}"x 10^{1/8}"
- UPC: 9800L 0-8316237588-9
- 9805L 0-8316237688-6
- 9810L 0-8316237888-0
- 9815L 0-8316237988-7
- Shipping Weight - 15.4 lbs.

► **LIGHTING**

Center mounted 100 watt maximum schoolhouse light kit.
Light kit and fan are shipped in one carton. (bulb not included)

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY			DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 1-877-304-3785
Fax: (610) 696-4648

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015